

POULIES MOYEUX AMOVIBLES

- 14M -

Pour courroie largeur 40 mm														
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	P	L	Moyeu	Ales. Max
Fonte ou Acier	28-14M-40	B108	4F	28	124.78	121.98	127	-	98	54	11.0	32	2012	50
	29-14M-40	B43	4F	29	129.24	126.44	138	-	100	54	11.0	32	2012	50
	30-14M-40	B43	4F	30	133.69	130.89	138	-	100	54	11.0	32	2012	50
	32-14M-40	B45	4F	32	142.61	139.81	154	-	104	54	11.0	32	2012	50
	34-14M-40	B46	4F	34	151.52	148.72	160	-	110	54	4.5	45	2517	60
	36-14M-40	B47	4F	36	160.43	157.63	168	-	120	54	4.5	45	2517	60
	38-14M-40	B49	4F	38	169.35	166.55	183	-	130	54	4.5	45	2517	60
	40-14M-40	B50	4F	40	178.26	175.46	190	-	138	54	4.5	45	2517	60
	44-14M-40	B55	4F	44	196.08	193.28	211	-	155	54	1.5	51	3020	75
	48-14M-40	B57	4F	48	213.91	211.11	225	-	170	54	1.5	51	3020	75
	56-14M-40	B61	9WF	56	249.56	246.76	256	170	208	54	1.5	51	3020	75
	64-14M-40	B64	9WF	64	285.21	282.41	296	170	242	54	1.5	51	3020	75
	72-14M-40	-	9W	72	320.87	318.07	-	170	280	54	1.5	51	3020	75
Fonte	80-14M-40	-	9A	80	356.52	353.72	-	170	315	54	1.5	51	3020	75
	90-14M-40	-	9A	90	401.08	398.28	-	170	360	54	1.5	51	3020	75
	112-14M-40	-	9A	112	499.12	496.32	-	170	457	54	1.5	51	3020	75
	144-14M-40	-	9A	144	641.73	638.93	-	170	600	54	1.5	51	3020	75
	168-14M-40	-	9A	168	748.69	745.89	-	170	706	54	1.5	51	3020	75
	192-14M-40	-	9A	192	855.64	852.84	-	170	813	54	1.5	51	3020	75
	216-14M-40	-	9A	216	962.59	959.80	-	170	920	54	1.5	51	3020	75

Pour courroie largeur 55 mm														
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	P	L	Moyeu	Ales. Max
Fonte ou Acier	28-14M-55	B108	4F	28	124.78	121.98	127	-	98	70	19.0	32	2012	50
	29-14M-55	B43	4F	29	129.24	126.44	138	-	100	70	19.0	32	2012	50
	30-14M-55	B43	4F	30	133.69	130.89	138	-	100	70	12.5	45	2517	60
	32-14M-55	B45	4F	32	142.61	139.81	154	-	108	70	12.5	45	2517	60
	34-14M-55	B46	4F	34	151.52	148.72	160	-	110	70	12.5	45	2517	60
	36-14M-55	B47	4F	36	160.43	157.63	168	-	120	70	12.5	45	2517	60
	38-14M-55	B49	4F	38	169.35	166.55	183	-	130	70	12.5	45	2517	60
	40-14M-55	B50	4F	40	178.26	175.46	190	-	138	70	12.5	45	2517	60
	44-14M-55	B55	4F	44	196.08	193.28	211	-	155	70	9.5	51	3020	75
	48-14M-55	B57	4F	48	213.91	211.11	225	-	170	70	9.5	51	3020	75
	56-14M-55	B61	9WF	56	249.56	246.76	256	170	208	70	9.5	51	3020	75
	64-14M-55	B64	9WF	64	285.21	282.41	296	170	242	70	9.5	51	3020	75
	72-14M-55	-	9W	72	320.87	318.07	-	170	280	70	9.5	51	3020	75
Fonte	80-14M-55	-	9A	80	356.52	353.72	-	170	315	70	9.5	51	3020	75
	90-14M-55	-	9A	90	401.08	398.28	-	170	360	70	9.5	51	3020	75
	112-14M-55	-	9A	112	499.12	496.32	-	170	457	70	9.5	51	3020	75
	144-14M-55	-	9A	144	641.73	638.93	-	170	600	70	9.5	51	3020	75
	168-14M-55	-	9A	168	748.69	745.89	-	170	706	70	9.5	51	3020	75
	192-14M-55	-	9A	192	855.64	852.84	-	170	813	70	9.5	51	3020	75
	216-14M-55	-	7A	216	962.59	959.80	-	190	920	70	9.5	89	3535	90

POULIES MOYEUX AMOVIBLES

- 14M -

Pour courroie largeur 85 mm														
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	P	L	Moyeu	Ales. Max
Fonte ou Acier	28-14M-85	B108	4F	28	124.78	121.98	127	-	98	102	28.5	45	2517	60
	29-14M-85	B43	4F	29	129.24	126.44	138	-	100	102	28.5	45	2517	60
	30-14M-85	B43	4F	30	133.69	130.89	138	-	100	102	28.5	45	2517	60
	32-14M-85	B45	4F	32	142.61	139.81	154	-	108	102	28.5	45	2517	60
	34-14M-85	B46	4F	34	151.52	148.72	160	-	110	102	28.5	45	2517	60
	36-14M-85	B47	4F	36	160.43	157.63	168	-	125	102	25.5	51	3020	75
	38-14M-85	B49	4F	38	169.35	166.55	183	-	130	102	25.5	51	3020	75
	40-14M-85	B50	4F	40	178.26	175.46	190	-	138	102	25.5	51	3020	75
	44-14M-85	B55	4F	44	196.08	193.28	211	-	155	102	13	76	3030	75
	48-14M-85	B57	4F	48	213.91	211.11	225	-	170	102	13	76	3030	75
	56-14M-85	B61	4F	56	249.56	246.76	256	-	210	102	18.5	65	3525	90
	64-14M-85	B64	9WF	64	285.21	282.41	296	190	242	102	18.5	65	3525	90
	72-14M-85	-	9W	72	320.87	318.07	-	190	280	102	18.5	65	3525	90
Fonte	80-14M-85	-	9A	80	356.52	353.72	-	190	315	102	18.5	65	3525	90
	90-14M-85	-	9A	90	401.08	398.28	-	190	360	102	18.5	65	3525	90
	112-14M-85	-	9A	112	499.12	496.32	-	190	457	102	18.5	65	3525	90
	144-14M-85	-	9A	144	641.73	638.93	-	190	600	102	18.5	65	3525	90
	168-14M-85	-	9A	168	748.69	745.89	-	190	706	102	18.5	65	3525	90
	192-14M-85	-	3A	192	855.64	852.84	-	230	813	102	-	102	4040	100
	216-14M-85	-	3A	216	962.59	959.80	-	230	920	102	-	102	4040	100

Pour courroie largeur 115 mm														
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	P	L	Moyeu	Ales. Max
Fonte ou Acier	28-14M-115	B108	4F	28	124.78	121.98	127	-	98	133	44	45	2517	60
	29-14M-115	B43	4F	29	129.24	126.44	138	-	100	133	44	45	2517	60
	30-14M-115	B43	4F	30	133.69	130.89	138	-	100	133	44	45	2517	60
	32-14M-115	B45	4F	32	142.61	139.81	154	-	108	133	44	45	2517	60
	34-14M-115	B46	4F	34	151.52	148.72	160	-	110	133	44	45	2517	60
	36-14M-115	B47	4F	36	160.43	157.63	168	-	125	133	41	51	3020	75
	38-14M-115	B49	4F	38	169.35	166.55	183	-	130	133	41	51	3020	75
	40-14M-115	B50	4F	40	178.26	175.46	190	-	140	133	41	51	3020	75
	44-14M-115	B55	4F	44	196.08	193.28	211	-	155	133	28.5	76	3030	75
	48-14M-115	B57	4F	48	213.91	211.11	225	-	170	133	28.5	76	3030	75
	56-14M-115	B61	4F	56	249.56	246.76	256	-	210	133	22	89	3535	90
	64-14M-115	B64	9WF	64	285.21	282.41	296	190	242	133	22	89	3535	90
	72-14M-115	-	9W	72	320.87	318.07	-	190	280	133	22	89	3535	90
Fonte	80-14M-115	-	9A	80	356.52	353.72	-	190	315	133	22	89	3535	90
	90-14M-115	-	9A	90	401.08	398.28	-	190	360	133	22	89	3535	90
	112-14M-115	-	9A	112	499.12	496.32	-	190	457	133	22	89	3535	90
	144-14M-115	-	9A	144	641.73	638.93	-	230	600	133	15.5	102	4040	100
	168-14M-115	-	9A	168	748.69	745.89	-	230	706	133	15.5	102	4040	100
	192-14M-115	-	9A	192	855.64	852.84	-	230	813	133	15.5	102	4040	100
	216-14M-115	-	9A	216	962.59	959.80	-	230	920	133	15.5	102	4040	100

POULIES MOYEUX AMOVIBLES

- 14M -

Pour courroie largeur 170 mm														
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	P	L	Moyeu	Ales. Max
Fonte ou Acier	38-14M-170	B49	4F	38	169.35	166.55	183	-	130	187	55.5	76	3030	75
	40-14M-170	B50	4F	40	178.26	175.46	190	-	140	187	55.5	76	3030	75
	44-14M-170	B55	4F	44	196.08	193.28	211	-	155	187	49	89	3535	90
	48-14M-170	B57	4F	48	213.91	211.11	225	-	175	187	49	89	3535	90
	56-14M-170	B61	4F	56	249.56	246.76	256	-	210	187	49	89	3535	90
	64-14M-170	B64	4F	64	285.21	282.41	296	-	240	187	42.5	102	4040	100
Fonte	72-14M-170	-	9W	72	320.87	318.07	-	230	280	187	42.5	102	4040	100
	80-14M-170	-	9W	80	356.52	353.72	-	230	315	187	42.5	102	4040	100
	90-14M-170	-	9A	90	401.08	398.28	-	230	360	187	42.5	102	4040	100
	112-14M-170	-	9A	112	499.12	496.32	-	265	456	187	30	127	5050	125
	144-14M-170	-	9A	144	641.73	638.93	-	265	600	187	30	127	5050	125
	168-14M-170	-	9A	168	748.69	745.89	-	265	706	187	30	127	5050	125
	192-14M-170	-	9A	192	855.64	852.84	-	265	813	187	30	127	5050	125
	216-14M-170	-	9A	216	962.59	959.80	-	265	920	187	30	127	5050	125

