

POULIES MOYEUX AMOVIBLES

- 5M -

Pour courroie largeur 15 mm														
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	P	L	Moyeu	Ales. Max
Acier	34-5M-15	B12	8F	34	54.11	52.97	57	43	-	20.5	1.5	22	1008	25
	36-5M-15	B13	8F	36	57.30	56.16	60	44	-	20.5	1.5	22	1108	25
	38-5M-15	B15	8F	38	60.48	59.34	66	48	-	20.5	1.5	22	1108	25
	40-5M-15	B16	8F	40	63.66	62.52	71	52	-	20.5	1.5	22	1108	25
	44-5M-15	B17	8F	44	70.03	68.89	75	54	-	20.5	1.5	22	1108	25
	48-5M-15	B19	8F	48	76.40	75.26	83	64	-	20.5	4.5	25	1210	32
Fonte	56-5M-15	B22	8F	56	89.13	87.99	93	70	-	20.5	4.5	25	1210	32
	64-5M-15	B25	8F	64	101.86	100.72	106	78	-	20.5	4.5	25	1210	32
	72-5M-15	B28	8F	72	114.59	113.45	119	90	-	20.5	4.5	25	1610	42
	80-5M-15	B32	8F	80	127.33	126.19	135	92	-	20.5	4.5	25	1610	42
	90-5M-15	-	7W	90	143.24	142.10	-	92	126	20.5	2.25	25	1610	42
	112-5M-15	-	7W	112	178.26	177.12	-	92	162	20.5	2.25	25	1610	42
	136-5M-15	-	7W	136	216.46	215.32	-	-	199	20.5	5.75	32	2012	50

