

POULIES PRÉALÉSEES

- L -

Pour courroie largeur 12,7 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	10 L 050 F	B5	6F	10	30.32	29.55	36	20	-	19	28	8
	11 L 050 F	B6	6F	11	33.35	32.58	38	24	-	19	30	8
	12 L 050 F	B7	6F	12	36.38	35.61	42	26	-	19	30	8
	13 L 050 F	B8	6F	13	39.42	38.65	44	28	-	19	30	8
	14 L 050 F	B9	6F	14	42.45	41.68	48	28	-	19	30	8
	15 L 050 F	B10	6F	15	45.48	44.71	51	34	-	19	30	8
	16 L 050 F	B11	6F	16	48.51	47.74	54	36	-	19	32	8
	17 L 050 F	B12	6F	17	51.54	50.77	57	36	-	19	32	10
	18 L 050 F	B13	6F	18	54.58	53.81	60	40	-	19	32	10
	19 L 050 F	B14	6F	19	57.61	56.84	63	40	-	19	32	10
	20 L 050 F	B15	6F	20	60.64	59.87	66	45	-	19	32	10
	21 L 050 F	B16	6F	21	63.67	62.90	71	45	-	19	32	10
	22 L 050 F	B17	6F	22	66.70	65.93	75	45	-	19	32	10
	23 L 050 F	B18	6F	23	69.74	68.97	79	55	-	19	32	12
	24 L 050 F	B18	6F	24	72.77	72.00	79	55	-	19	32	12
	25 L 050 F	B19	6F	25	75.80	75.03	83	58	-	19	32	12
	26 L 050 F	B20	6F	26	78.83	78.06	87	58	-	19	32	12
	27 L 050 F	B20	6F	27	81.86	81.09	87	58	-	19	32	12
	28 L 050 F	B21	6F	28	84.90	84.13	91	58	-	19	32	12
	29 L 050 F	B22	6F	29	87.93	87.16	93	58	-	19	32	12
	30 L 050 F	B23	6F	30	90.96	90.19	97	70	-	19	32	12
	32 L 050 F	B24	6F	32	97.02	96.25	103	70	-	19	32	12
	34 L 050 F	B26	6F	34	103.09	102.32	111	70	-	19	32	12
	35 L 050 F	B26	6F	35	106.12	105.35	111	70	-	19	32	12
	36 L 050 F	B27	6F	36	109.15	108.38	115	70	-	19	32	12
Fonte ou Acier	40 L 050 F	B30	6F/6WF	40	121.28	120.51	127	70	100	19	32	15
	42 L 050 F	B32	6F/6WF	42	127.34	126.57	135	70	106	19	32	15
	44 L 050 F	B33/34	6F/6WF	44	133.41	132.64	142	70	112	19	32	15
	45 L 050 F	B33/34	6F/6WF	45	136.44	135.67	142	70	115	19	32	15
	48 L 050 F	B36	6F/6WF	48	145.54	144.77	152	70	124	19	32	15
Fonte	60 L 050	-	6W	60	181.92	181.15	-	75	160	19	42	15
	72 L 050	-	6W	72	218.30	217.53	-	75	197	19	42	15

Pour courroie largeur 19,05 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	10 L 075 F	B5	6F	10	30.32	29.55	36	20	-	25.4	38	8
	11 L 075 F	B6	6F	11	33.35	32.58	38	24	-	25.4	38	8
	12 L 075 F	B7	6F	12	36.38	35.61	42	26	-	25.4	38	8
	13 L 075 F	B8	6F	13	39.42	38.65	44	28	-	25.4	38	8
	14 L 075 F	B9	6F	14	42.45	41.68	48	28	-	25.4	38	8
	15 L 075 F	B10	6F	15	45.48	44.71	51	34	-	25.4	38	8
	16 L 075 F	B11	6F	16	48.51	47.74	54	36	-	25.4	38	8
	17 L 075 F	B12	6F	17	51.54	50.77	57	36	-	25.4	38	10
	18 L 075 F	B13	6F	18	54.58	53.81	60	40	-	25.4	38	10
	19 L 075 F	B14	6F	19	57.61	56.84	63	40	-	25.4	38	10
	20 L 075 F	B15	6F	20	60.64	59.87	66	45	-	25.4	38	10
	21 L 075 F	B16	6F	21	63.67	62.90	71	45	-	25.4	38	10
	22 L 075 F	B17	6F	22	66.70	65.93	75	45	-	25.4	38	10
	23 L 075 F	B18	6F	23	69.74	68.97	79	55	-	25.4	38	12
	24 L 075 F	B18	6F	24	72.77	72.00	79	55	-	25.4	38	12
	25 L 075 F	B19	6F	25	75.80	75.03	83	58	-	25.4	38	12
	26 L 075 F	B20	6F	26	78.83	78.06	87	58	-	25.4	38	12
	27 L 075 F	B20	6F	27	81.86	81.09	87	58	-	25.4	38	12
	28 L 075 F	B21	6F	28	84.90	84.13	91	58	-	25.4	38	12
	29 L 075 F	B22	6F	29	87.93	87.16	93	58	-	25.4	38	12
	30 L 075 F	B23	6F	30	90.96	90.19	97	70	-	25.4	38	12
	32 L 075 F	B24	6F	32	97.02	96.25	103	70	-	25.4	38	12
	34 L 075 F	B26	6F	34	103.09	102.32	111	70	-	25.4	38	12
	35 L 075 F	B26	6F	35	106.12	105.35	111	70	-	25.4	38	12
	36 L 075 F	B27	6F	36	109.15	108.38	115	70	-	25.4	38	12
Fonte ou Acier	40 L 075 F	B30	6F/6WF	40	121.28	120.51	127	70	100	25.4	38	15
	42 L 075 F	B32	6F/6WF	42	127.34	126.57	135	70	106	25.4	38	15
	44 L 075 F	B33/34	6F/6WF	44	133.41	132.64	142	70	112	25.4	38	15
	45 L 075 F	B33/34	6F/6WF	45	136.44	135.67	142	70	115	25.4	38	15
	48 L 075 F	B36	6F/6WF	48	145.54	144.77	152	70	124	25.4	38	15
Fonte	60 L 075	-	6W	60	181.92	181.15	-	75	160	25.4	45	15
	72 L 075	-	6W	72	218.30	217.53	-	75	197	25.4	45	15

POULIES PRÉALÉSÉES

- L -

Pour courroie largeur 25,4 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	10 L 100 F	B5	6F	10	30.32	29.55	36	20	-	31.8	45	8
	11 L 100 F	B6	6F	11	33.35	32.58	38	24	-	31.8	45	8
	12 L 100 F	B7	6F	12	36.38	35.61	42	26	-	31.8	45	8
	13 L 100 F	B8	6F	13	39.42	38.65	44	28	-	31.8	45	8
	14 L 100 F	B9	6F	14	42.45	41.68	48	28	-	31.8	45	8
	15 L 100 F	B10	6F	15	45.48	44.71	51	34	-	31.8	45	8
	16 L 100 F	B11	6F	16	48.51	47.74	54	36	-	31.8	45	8
	17 L 100 F	B12	6F	17	51.54	50.77	57	36	-	31.8	45	10
	18 L 100 F	B13	6F	18	54.58	53.81	60	40	-	31.8	45	10
	19 L 100 F	B14	6F	19	57.61	56.84	63	40	-	31.8	45	10
	20 L 100 F	B15	6F	20	60.64	59.87	66	45	-	31.8	45	10
	21 L 100 F	B16	6F	21	63.67	62.90	71	45	-	31.8	45	10
	22 L 100 F	B17	6F	22	66.70	65.93	75	45	-	31.8	45	10
	23 L 100 F	B18	6F	23	69.74	68.97	79	55	-	31.8	45	12
	24 L 100 F	B18	6F	24	72.77	72.00	79	55	-	31.8	45	12
	25 L 100 F	B19	6F	25	75.80	75.03	83	58	-	31.8	45	12
	26 L 100 F	B20	6F	26	78.83	78.06	87	58	-	31.8	45	12
	27 L 100 F	B20	6F	27	81.86	81.09	87	58	-	31.8	45	12
	28 L 100 F	B21	6F	28	84.90	84.13	91	58	-	31.8	45	12
	29 L 100 F	B22	6F	29	87.93	87.16	93	58	-	31.8	45	12
	30 L 100 F	B23	6F	30	90.96	90.19	97	70	-	31.8	45	12
	32 L 100 F	B24	6F	32	97.02	96.25	103	70	-	31.8	45	12
	34 L 100 F	B26	6F	34	103.09	102.32	111	70	-	31.8	45	12
	35 L 100 F	B26	6F	35	106.12	105.35	111	70	-	31.8	45	12
	36 L 100 F	B27	6F	36	109.15	108.38	115	70	-	31.8	45	12
Fonte ou Acier	40 L 100 F	B30	6F/6WF	40	121.28	120.51	127	70	100	31.8	45	15
	42 L 100 F	B32	6F/6WF	42	127.34	126.57	135	70	106	31.8	45	15
	44 L 100 F	B33/34	6F/6WF	44	133.41	132.64	142	70	112	31.8	45	15
	45 L 100 F	B33/34	6F/6WF	45	136.44	135.67	142	70	115	31.8	45	15
	48 L 100 F	B36	6F/6WF	48	145.54	144.77	152	70	124	31.8	45	15
Fonte	60 L 100	-	6W	60	181.92	181.15	-	75	160	31.8	50	15
	72 L 100	-	6W	72	218.30	217.53	-	75	197	31.8	50	15

