

POULIES PRÉALÉSÉES

- 14M -

Pour courroie largeur 40 mm												
Fonte ou Acier	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	28-14M-40	B108	6F	28	124.78	121.98	127	100	-	54	69	24
	29-14M-40	B43	6F	29	129.24	126.44	138	100	-	54	69	24
	30-14M-40	B43	6F	30	133.69	130.89	138	100	-	54	69	24
	32-14M-40	B45	6F	32	142.61	139.81	154	100	-	54	69	24
	34-14M-40	B46	6F	34	151.52	148.72	160	100	-	54	69	24
	36-14M-40	B47	6F	36	160.43	157.63	168	100	-	54	69	24
	38-14M-40	B49	6F	38	169.35	166.55	183	120	-	54	69	24
	40-14M-40	B50	6F	40	178.26	175.46	190	120	-	54	69	24
	44-14M-40	B55	6F	44	196.08	193.28	211	120	-	54	69	24
Fonte	48-14M-40	B57	6WF	48	213.91	211.11	225	135	172	54	69	24
	56-14M-40	B61	6WF	56	249.56	246.76	256	135	207	54	69	28
	64-14M-40	B64	6WF	64	285.21	282.41	296	135	242	54	69	28
	72-14M-40	-	6A	72	320.87	318.07	-	135	278	54	69	28
	80-14M-40	-	6A	80	356.52	353.72	-	135	314	54	69	28
	90-14M-40	-	6A	90	401.08	398.28	-	135	358	54	69	28
	112-14M-40	-	6A	112	499.12	496.32	-	135	456	54	69	28
	144-14M-40	-	6A	144	641.73	638.93	-	135	600	54	69	28
	168-14M-40	-	6A	168	748.69	745.89	-	135	706	54	69	28
	192-14M-40	-	6A	192	855.64	852.84	-	135	813	54	69	28
	216-14M-40	-	6A	216	962.59	959.80	-	150	920	54	69	28

Pour courroie largeur 55 mm												
Fonte ou Acier	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	28-14M-55	B108	6F	28	124.78	121.98	127	100	-	70	85	24
	29-14M-55	B43	6F	29	129.24	126.44	138	100	-	70	85	24
	30-14M-55	B43	6F	30	133.69	130.89	138	100	-	70	85	24
	32-14M-55	B45	6F	32	142.61	139.81	154	100	-	70	85	24
	34-14M-55	B46	6F	34	151.52	148.72	160	100	-	70	85	24
	36-14M-55	B47	6F	36	160.43	157.63	168	100	-	70	85	24
	38-14M-55	B49	6F	38	169.35	166.55	183	120	-	70	85	24
	40-14M-55	B50	6F	40	178.26	175.46	190	120	-	70	85	24
	44-14M-55	B55	6F	44	196.08	193.28	211	120	-	70	85	24
Fonte	48-14M-55	B57	10WF	48	213.91	211.11	225	135	172	70	70	24
	56-14M-55	B61	10WF	56	249.56	246.76	256	135	207	70	70	28
	60-14M-55	B65/66	10WF	60	267.39	264.59	274	135	225	70	70	28
	64-14M-55	B64	10WF	64	285.21	282.41	296	135	242	70	70	28
	72-14M-55	-	10A	72	320.87	318.07	-	135	278	70	70	28
	80-14M-55	-	10A	80	356.52	353.72	-	135	314	70	70	28
	90-14M-55	-	10A	90	401.08	398.28	-	135	358	70	70	28
	112-14M-55	-	10A	112	499.12	496.32	-	135	456	70	70	28
	144-14M-55	-	10A	144	641.73	638.93	-	135	600	70	70	28
	168-14M-55	-	10A	168	748.69	745.89	-	135	706	70	70	28
	192-14M-55	-	10A	192	855.64	852.84	-	135	813	70	70	28
	216-14M-55	-	10A	216	962.59	959.80	-	150	920	70	70	28

POULIES PRÉALÉSÉES

- 14M -

Pour courroie largeur 85 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Fonte ou Acier	28-14M-85	B108	6F	28	124.78	121.98	127	100	-	102	117	24
	29-14M-85	B43	6F	29	129.24	126.44	138	100	-	102	117	24
	30-14M-85	B43	6F	30	133.69	130.89	138	100	-	102	117	24
	32-14M-85	B45	6F	32	142.61	139.81	154	100	-	102	117	24
	34-14M-85	B46	6F	34	151.52	148.72	160	100	-	102	117	24
	36-14M-85	B47	6F	36	160.43	157.63	168	100	-	102	117	24
	38-14M-85	B49	6F	38	169.35	166.55	183	120	-	102	117	24
	40-14M-85	B50	6F	40	178.26	175.46	190	135	-	102	117	24
	44-14M-85	B55	6F	44	196.08	193.28	211	135	-	102	117	24
	48-14M-85	B57	6F	48	213.91	211.11	225	150	-	102	117	24
Fonte	56-14M-85	B61	10WF	56	249.56	246.76	256	150	207	102	102	28
	64-14M-85	B64	10WF	64	285.21	282.41	296	150	242	102	102	28
	72-14M-85	-	10A	72	320.87	318.07	-	150	278	102	102	28
	80-14M-85	-	10A	80	356.52	353.72	-	150	314	102	102	28
	90-14M-85	-	10A	90	401.08	398.28	-	150	358	102	102	28
	112-14M-85	-	10A	112	499.12	496.32	-	150	456	102	102	28
	144-14M-85	-	10A	144	641.73	638.93	-	150	600	102	102	28
	168-14M-85	-	10A	168	748.69	745.89	-	150	706	102	102	28
	192-14M-85	-	10A	192	855.64	852.84	-	165	813	102	102	28
	216-14M-85	-	10A	216	962.59	959.80	-	165	920	102	102	28

Pour courroie largeur 115 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Fonte ou Acier	28-14M-115	B108	6F	28	124.78	121.98	127	100	-	133	148	32
	29-14M-115	B43	6F	29	129.24	126.44	138	100	-	133	148	32
	30-14M-115	B43	6F	30	133.69	130.89	138	100	-	133	148	32
	32-14M-115	B45	6F	32	142.61	139.81	154	100	-	133	148	32
	34-14M-115	B46	6F	34	151.52	148.72	160	100	-	133	148	32
	36-14M-115	B47	6F	36	160.43	157.63	168	120	-	133	148	32
	38-14M-115	B49	6F	38	169.35	166.55	183	120	-	133	148	32
	40-14M-115	B50	6F	40	178.26	175.46	190	135	-	133	148	32
	44-14M-115	B55	6F	44	196.08	193.28	211	140	-	133	148	32
	48-14M-115	B57	6F	48	213.91	211.11	225	150	-	133	148	32
	56-14M-115	B61	6F	56	249.56	246.76	256	150	-	133	148	32
Fonte	64-14M-115	B64	10WF	64	285.21	282.41	296	150	242	133	133	32
	72-14M-115	-	10A	72	320.87	318.07	-	150	278	133	133	32
	80-14M-115	-	10A	80	356.52	353.72	-	150	314	133	133	32
	90-14M-115	-	10A	90	401.08	398.28	-	150	358	133	133	32
	112-14M-115	-	10A	112	499.12	496.32	-	150	456	133	133	32
	144-14M-115	-	10A	144	641.73	638.93	-	165	600	133	133	32
	168-14M-115	-	10A	168	748.69	745.89	-	165	706	133	133	32
	192-14M-115	-	10A	192	855.64	852.84	-	165	813	133	133	32
	216-14M-115	-	10A	216	962.59	959.80	-	165	920	133	133	32

POULIES PRÉALÉSÉES

- 14M -

Pour courroie largeur 170 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Fonte ou Acier	28-14M-170	B108	6F	28	124.78	121.98	127	100	-	187	202	32
	29-14M-170	B43	6F	29	129.24	126.44	138	100	-	187	202	32
	30-14M-170	B43	6F	30	133.69	130.89	138	100	-	187	202	32
	32-14M-170	B45	6F	32	142.61	139.81	154	100	-	187	202	32
	34-14M-170	B46	6F	34	151.52	148.72	160	100	-	187	202	32
	36-14M-170	B47	6F	36	160.43	157.63	168	120	-	187	202	32
	38-14M-170	B49	6F	38	169.35	166.55	183	135	-	187	202	32
	40-14M-170	B50	6F	40	178.26	175.46	190	140	-	187	202	32
	44-14M-170	B55	6F	44	196.08	193.28	211	160	-	187	202	32
	48-14M-170	B57	6F	48	213.91	211.11	225	160	-	187	202	32
	56-14M-170	B61	6F	56	249.56	246.76	256	160	-	187	202	32
	64-14M-170	B64	6F	64	285.21	282.41	296	180	-	187	202	32
Fonte	72-14M-170	-	10W	72	320.87	318.07	-	180	278	187	187	32
	80-14M-170	-	10W	80	356.52	353.72	-	180	314	187	187	32
	90-14M-170	-	10A	90	401.08	398.28	-	180	358	187	187	38
	112-14M-170	-	10A	112	499.12	496.32	-	200	456	187	187	38
	144-14M-170	-	10A	144	641.73	638.93	-	220	600	187	187	38
	168-14M-170	-	10A	168	748.69	745.89	-	220	706	187	187	38
	192-14M-170	-	10A	192	855.64	852.84	-	220	813	187	187	38
	216-14M-170	-	10A	216	962.59	959.80	-	220	920	187	187	38

