

POULIES PRÉALÉSÉES

- AT10 -

Pour courroie largeur 16 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	31AT10/15-2	B10	6F	15	47.75	45.90	51	32	-	21	31	8
	31AT10/16-2	B11	6F	16	50.93	49.08	54	35	-	21	31	8
	31AT10/18-2	B13	6F	18	57.30	55.45	60	40	-	21	31	8
	31AT10/19-2	B15	6F	19	60.48	58.63	66	44	-	21	31	8
	31AT10/20-2	B15	6F	20	63.66	61.81	66	46	-	21	31	8
	31AT10/22-2	B17	6F	22	70.03	68.18	75	52	-	21	31	8
	31AT10/24-2	B19	6F	24	76.40	74.55	83	58	-	21	31	8
	31AT10/25-2	B19	6F	25	79.58	77.73	83	60	-	21	31	8
	31AT10/26-2	B20	6F	26	82.76	80.91	87	60	-	21	31	8
	31AT10/27-2	B21	6F	27	85.95	84.10	91	60	-	21	31	8
	31AT10/28-2	B22	6F	28	89.13	87.28	93	60	-	21	31	8
	31AT10/30-2	B23	6F	30	95.50	93.65	97	60	-	21	31	8
	31AT10/32-2	B25	6F	32	101.86	100.01	106	65	-	21	31	10
	31AT10/36-2	B28	6F	36	114.59	112.74	119	70	-	21	31	10
	31AT10/40-2	B31	6F	40	127.33	125.48	131	80	-	21	31	10
	31AT10/44-0	-	6	44	140.06	138.21	-	88	-	21	31	10
	31AT10/48-0	-	6	48	152.79	150.94	-	95	-	21	31	16
	31AT10/60-0	-	6	60	190.99	189.14	-	110	-	21	31	16
	31AT10/44-0	-	6W	44	140.06	138.21	-	75	118	21	31	10
	31AT10/48-0	-	6W	48	152.79	150.94	-	80	132	21	31	16
	31AT10/60-0	-	6W	60	190.99	189.14	-	90	172	21	31	16

Pour courroie largeur 25 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	40AT10/15-2	B10	6F	15	47.75	45.90	51	32	-	30	40	8
	40AT10/16-2	B11	6F	16	50.93	49.08	54	35	-	30	40	8
	40AT10/18-2	B13	6F	18	57.30	55.45	60	40	-	30	40	8
	40AT10/19-2	B15	6F	19	60.48	58.63	66	44	-	30	40	8
	40AT10/20-2	B15	6F	20	63.66	61.81	66	46	-	30	40	8
	40AT10/22-2	B17	6F	22	70.03	68.18	75	52	-	30	40	8
	40AT10/24-2	B19	6F	24	76.40	74.55	83	58	-	30	40	8
	40AT10/25-2	B19	6F	25	79.58	77.73	83	60	-	30	40	8
	40AT10/26-2	B20	6F	26	82.76	80.91	87	60	-	30	40	8
	40AT10/27-2	B21	6F	27	85.95	84.10	91	60	-	30	40	8
	40AT10/28-2	B22	6F	28	89.13	87.28	93	60	-	30	40	8
	40AT10/30-2	B23	6F	30	95.50	93.65	97	60	-	30	40	8
	40AT10/32-2	B25	6F	32	101.86	100.01	106	65	-	30	40	10
	40AT10/36-2	B28	6F	36	114.59	112.74	119	70	-	30	40	10
	40AT10/40-2	B31	6F	40	127.33	125.48	131	80	-	30	40	10
	40AT10/44-0	-	6	44	140.06	138.21	-	88	-	30	40	10
	40AT10/48-0	-	6	48	152.79	150.94	-	95	-	30	40	16
	40AT10/60-0	-	6	60	190.99	189.14	-	110	-	30	40	16
	40AT10/44-0	-	6W	44	140.06	138.21	-	75	118	30	40	10
	40AT10/48-0	-	6W	48	152.79	150.94	-	80	132	30	40	16
	40AT10/60-0	-	6W	60	190.99	189.14	-	90	172	30	40	16

POULIES PRÉALÉSÉES

- AT10 -

Pour courroie largeur 32 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	47AT10/18-2	B13	6F	18	57.30	55.45	60	40	-	37	47	10
	47AT10/19-2	B15	6F	19	60.48	58.63	66	44	-	37	47	10
	47AT10/20-2	B15	6F	20	63.66	61.81	66	46	-	37	47	12
	47AT10/22-2	B17	6F	22	70.03	68.18	75	52	-	37	47	12
	47AT10/24-2	B19	6F	24	76.40	74.55	83	58	-	37	47	12
	47AT10/25-2	B19	6F	25	79.58	77.73	83	60	-	37	47	12
	47AT10/26-2	B20	6F	26	82.76	80.91	87	60	-	37	47	12
	47AT10/27-2	B21	6F	27	85.95	84.10	91	60	-	37	47	12
	47AT10/28-2	B22	6F	28	89.13	87.28	93	60	-	37	47	12
	47AT10/30-2	B23	6F	30	95.50	93.65	97	60	-	37	47	12
	47AT10/32-2	B25	6F	32	101.86	100.01	106	65	-	37	47	12
	47AT10/36-2	B28	6F	36	114.59	112.74	119	70	-	37	47	16
	47AT10/40-2	B31	6F	40	127.33	125.48	131	80	-	37	47	16
	47AT10/44-0	-	6	44	140.06	138.21	-	88	-	37	47	16
	47AT10/48-0	-	6	48	152.79	150.94	-	95	-	37	47	16
	47AT10/60-0	-	6	60	190.99	189.14	-	110	-	37	47	16
	47AT10/44-0	-	6W	44	140.06	138.21	-	75	118	37	47	16
	47AT10/48-0	-	6W	48	152.79	150.94	-	80	132	37	47	16
	47AT10/60-0	-	6W	60	190.99	189.14	-	90	172	37	47	16

Pour courroie largeur 50 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	66AT10/18-2	B13	6F	18	57.30	55.45	60	40	-	56	66	10
	66AT10/19-2	B15	6F	19	60.48	58.63	66	44	-	56	66	10
	66AT10/20-2	B15	6F	20	63.66	61.81	66	46	-	56	66	12
	66AT10/22-2	B17	6F	22	70.03	68.18	75	52	-	56	66	12
	66AT10/24-2	B19	6F	24	76.40	74.55	83	58	-	56	66	12
	66AT10/25-2	B19	6F	25	79.58	77.73	83	60	-	56	66	12
	66AT10/26-2	B20	6F	26	82.76	80.91	87	60	-	56	66	12
	66AT10/27-2	B21	6F	27	85.95	84.10	91	60	-	56	66	12
	66AT10/28-2	B22	6F	28	89.13	87.28	93	60	-	56	66	12
	66AT10/30-2	B23	6F	30	95.50	93.65	97	60	-	56	66	12
	66AT10/32-2	B25	6F	32	101.86	100.01	106	65	-	56	66	12
	66AT10/36-2	B28	6F	36	114.59	112.74	119	70	-	56	66	16
	66AT10/40-2	B31	6F	40	127.33	125.48	131	80	-	56	66	16
	66AT10/44-0	-	6	44	140.06	138.21	-	88	-	56	66	16
	66AT10/48-0	-	6	48	152.79	150.94	-	95	-	56	66	16
	66AT10/60-0	-	6	60	190.99	189.14	-	110	-	56	66	16
	66AT10/44-0	-	6W	44	140.06	138.21	-	75	118	56	66	16
	66AT10/48-0	-	6W	48	152.79	150.94	-	80	132	56	66	16
	66AT10/60-0	-	6W	60	190.99	189.14	-	90	172	56	66	16

