

POULIES PRÉALÉSÉES

- AT5 -

Pour courroie largeur 10 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	21AT5/12-2	B1	6F	12	19.10	17.87	23	11	-	15	21	4
	21AT5/14-2	B2	6F	14	22.28	21.05	25	14	-	15	21	5
	21AT5/15-2	B3	6F	15	23.87	22.64	28	16	-	15	21	6
	21AT5/16-2	B4	6F	16	25.47	24.24	32	18	-	15	21	6
	21AT5/18-2	B4	6F	18	28.65	27.42	32	20	-	15	21	6
	21AT5/19-2	B5	6F	19	30.24	29.01	36	22	-	15	21	6
	21AT5/20-2	B5	6F	20	31.83	30.60	36	23	-	15	21	6
	21AT5/22-2	B6	6F	22	35.02	33.79	38	24	-	15	21	6
	21AT5/24-2	B7	6F	24	38.20	36.97	42	26	-	15	21	6
	21AT5/25-2	B8	6F	25	39.79	38.56	44	26	-	15	21	6
	21AT5/26-2	B8	6F	26	41.38	40.15	44	26	-	15	21	6
	21AT5/27-2	B9	6F	27	42.97	41.74	48	30	-	15	21	8
	21AT5/28-2	B9	6F	28	44.56	43.33	48	32	-	15	21	8
	21AT5/30-2	B10	6F	30	47.75	46.52	51	34	-	15	21	8
	21AT5/32-2	B11	6F	32	50.93	49.70	54	38	-	15	21	8
	21AT5/36-2	B14	6F	36	57.30	56.07	63	38	-	15	21	8
	21AT5/40-2	B15	6F	40	63.66	62.43	66	40	-	15	21	8
	21AT5/42-2	B16	6F	42	66.85	65.62	71	40	-	15	21	8
	21AT5/44-0	-	6	41	70.03	68.80	-	45	-	15	21	8
	21AT5/48-0	-	6	48	76.40	75.17	-	50	-	15	21	8
	21AT5/60-0	-	6	60	95.50	94.27	-	65	-	15	21	8
	21AT5/60-0	-	6W	60	95.50	94.27	-	50	82	15	21	8
	21AT5/72-0	-	6W	72	114.59	113.36	-	50	100	15	21	8

Pour courroie largeur 16 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	27AT5/12-2	B1	6F	12	19.10	17.87	23	11	-	21	27	4
	27AT5/14-2	B2	6F	14	22.28	21.05	25	14	-	21	27	5
	27AT5/15-2	B3	6F	15	23.87	22.64	28	16	-	21	27	5
	27AT5/16-2	B4	6F	16	25.47	24.24	32	18	-	21	27	6
	27AT5/18-2	B4	6F	18	28.65	27.42	32	20	-	21	27	6
	27AT5/19-2	B5	6F	19	30.24	29.01	36	22	-	21	27	6
	27AT5/20-2	B5	6F	20	31.83	30.60	36	23	-	21	27	6
	27AT5/22-2	B6	6F	22	35.02	33.79	38	24	-	21	27	6
	27AT5/24-2	B7	6F	24	38.20	36.97	42	26	-	21	27	6
	27AT5/25-2	B8	6F	25	39.79	38.56	44	26	-	21	27	6
	27AT5/26-2	B8	6F	26	41.38	40.15	44	26	-	21	27	6
	27AT5/27-2	B9	6F	27	42.97	41.74	48	30	-	21	27	8
	27AT5/28-2	B9	6F	28	44.56	43.33	48	32	-	21	27	8
	27AT5/30-2	B10	6F	30	47.75	46.52	51	34	-	21	27	8
	27AT5/32-2	B11	6F	32	50.93	49.70	54	38	-	21	27	8
	27AT5/36-2	B14	6F	36	57.30	56.07	63	38	-	21	27	8
	27AT5/40-2	B15	6F	40	63.66	62.43	66	40	-	21	27	8
	27AT5/42-2	B16	6F	42	66.85	65.62	71	40	-	21	27	8
	27AT5/44-0	-	6	44	70.03	68.80	-	45	-	21	27	8
	27AT5/48-0	-	6	48	76.40	75.17	-	50	-	21	27	8
	27AT5/60-0	-	6	60	95.50	94.27	-	65	-	21	27	8
	27AT5/60-0	-	6W	60	95.50	94.27	-	50	82	21	27	8
	27AT5/72-0	-	6W	72	114.59	113.36	-	50	100	21	27	8

POULIES PRÉALÉSÉES

- AT5 -

Pour courroie largeur 25 mm												
Aluminium	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
	36AT5/12-2	B1	6F	12	19.10	17.87	23	11	-	30	36	-
	36AT5/14-2	B2	6F	14	22.28	21.05	25	14	-	30	36	-
	36AT5/15-2	B3	6F	15	23.87	22.64	28	16	-	30	36	6
	36AT5/16-2	B4	6F	16	25.47	24.24	32	18	-	30	36	6
	36AT5/18-2	B4	6F	18	28.65	27.42	32	20	-	30	36	6
	36AT5/19-2	B5	6F	19	30.24	29.01	36	22	-	30	36	6
	36AT5/20-2	B5	6F	20	31.83	30.60	36	23	-	30	36	6
	36AT5/22-2	B6	6F	22	35.02	33.79	38	24	-	30	36	6
	36AT5/24-2	B7	6F	24	38.20	36.97	42	26	-	30	36	8
	36AT5/25-2	B8	6F	25	39.79	38.56	44	26	-	30	36	8
	36AT5/26-2	B8	6F	26	41.38	40.15	44	26	-	30	36	8
	36AT5/27-2	B9	6F	27	42.97	41.74	48	30	-	30	36	8
	36AT5/28-2	B9	6F	28	44.56	43.33	48	32	-	30	36	8
	36AT5/30-2	B10	6F	30	47.75	46.52	51	34	-	30	36	8
	36AT5/32-2	B11	6F	32	50.93	49.70	54	38	-	30	36	8
	36AT5/36-2	B14	6F	36	57.30	56.07	63	38	-	30	36	8
	36AT5/40-2	B15	6F	40	63.66	62.43	66	40	-	30	36	8
	36AT5/42-2	B16	6F	42	66.85	65.62	71	40	-	30	36	8
	36AT5/44-0	-	6	44	70.03	68.80	-	45	-	30	36	8
	36AT5/48-0	-	6	48	76.40	75.17	-	50	-	30	36	8
	36AT5/60-0	-	6	60	95.50	94.27	-	65	-	30	36	8
	36AT5/60-0	-	6W	60	95.50	94.27	-	50	82	30	36	8
	36AT5/72-0	-	6W	72	114.59	113.36	-	50	100	30	36	8

