

POULIES PRÉALÉSÉES

- H -

Pour courroie largeur 19,05 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	14 H 075 F	B14	6F	14	56.60	55.22	63	40	-	26.4	40	14/12
	15 H 075 F	B15	6F	15	60.64	59.26	66	45	-	26.4	40	14/12
	16 H 075 F	B16	6F	16	64.68	63.30	71	45	-	26.4	40	14/12
	17 H 075 F	B17	6F	17	68.73	67.35	75	45	-	26.4	40	14/12
	18 H 075 F	B18	6F	18	72.77	71.39	79	55	-	26.4	40	14/12
	19 H 075 F	B19	6F	19	76.81	75.43	83	60	-	26.4	40	14/12
	20 H 075 F	B20	6F	20	80.85	79.47	87	62	-	26.4	40	14/12
	21 H 075 F	B21	6F	21	84.90	83.52	91	65	-	26.4	40	14/12
	22 H 075 F	B22	6F	22	88.94	87.56	93	68	-	26.4	40	14/12
	23 H 075 F	B23	6F	23	92.98	91.60	97	72	-	26.4	40	14/12
	24 H 075 F	B24	6F	24	97.02	95.64	103	72	-	26.4	40	20/12
	25 H 075 F	B25	6F	25	101.07	99.69	106	72	-	26.4	40	20/15
	26 H 075 F	B26	6F	26	105.11	103.73	111	80	-	26.4	40	20/15
	27 H 075 F	B27	6F	27	109.15	107.77	115	80	-	26.4	40	20/15
	28 H 075 F	B28	6F	28	113.19	111.81	119	80	-	26.4	40	20/15
	29 H 075 F	B29	6F	29	117.24	115.86	123	80	-	26.4	40	20/15
	30 H 075 F	B30	6F	30	121.28	119.90	127	80	-	26.4	40	20/15
	32 H 075 F	B32	6F	32	129.36	127.98	135	80	-	26.4	40	20
	34 H 075 F	B33/34	6F	34	137.45	136.07	142	80	-	26.4	40	20
	35 H 075 F	B35	6F	35	141.49	140.11	148	80	-	26.4	40	20
Fonte ou Acier	36 H 075 F	B36	6F/6WF	36	145.54	144.16	152	80	118	26.4	40	20
	38 H 075 F	B37	6F/6WF	38	153.62	152.24	158	80	126	26.4	40	20
	40 H 075 F	B38	6F/6WF	40	161.71	160.33	168	80	134	26.4	40	20
Fonte	44 H 075 F	B40	6WF	44	177.88	176.50	184	80	150	26.4	40	20
	45 H 075 F	B41	6WF	45	181.92	180.54	192	80	154	26.4	40	20
	48 H 075 F	B42	6WF	48	194.05	192.67	200	90	166	26.4	40	20

Pour courroie largeur 25,4 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	14 H 100 F	B14	6F	14	56.60	55.22	63	40	-	31.8	45	14
	15 H 100 F	B15	6F	15	60.64	59.26	66	45	-	31.8	45	14
	16 H 100 F	B16	6F	16	64.68	63.30	71	45	-	31.8	45	14
	17 H 100 F	B17	6F	17	68.73	67.35	75	45	-	31.8	45	14
	18 H 100 F	B18	6F	18	72.77	71.39	79	55	-	31.8	45	14
	19 H 100 F	B19	6F	19	76.81	75.43	83	60	-	31.8	45	14
	20 H 100 F	B20	6F	20	80.85	79.47	87	62	-	31.8	45	14
	21 H 100 F	B21	6F	21	84.90	83.52	91	65	-	31.8	45	14
	22 H 100 F	B22	6F	22	88.94	87.56	93	68	-	31.8	45	14
	23 H 100 F	B23	6F	23	92.98	91.60	97	72	-	31.8	45	14
	24 H 100 F	B24	6F	24	97.02	95.64	103	72	-	31.8	45	20/14
	25 H 100 F	B25	6F	25	101.07	99.69	106	72	-	31.8	45	20/15
	26 H 100 F	B26	6F	26	105.11	103.73	111	80	-	31.8	45	20/15
	27 H 100 F	B27	6F	27	109.15	107.77	115	80	-	31.8	45	20/15
	28 H 100 F	B28	6F	28	113.19	111.81	119	80	-	31.8	45	20/15
	29 H 100 F	B29	6F	29	117.24	115.86	123	80	-	31.8	45	20/15
	30 H 100 F	B30	6F	30	121.28	119.90	127	80	-	31.8	45	20/15
	32 H 100 F	B32	6F	32	129.36	127.98	135	80	-	31.8	45	20
	34 H 100 F	B33/34	6F	34	137.45	136.07	142	80	-	31.8	45	20
	35 H 100 F	B35	6F	35	141.49	140.11	148	80	-	31.8	45	20
Fonte ou Acier	36 H 100 F	B36	6F/6WF	36	145.54	144.16	152	80	118	31.8	45	20
	38 H 100 F	B37	6F/6WF	38	153.62	152.24	158	80	126	31.8	45	20
	40 H 100 F	B38	6F/6WF	40	161.71	160.33	168	80	134	31.8	45	20
Fonte	44 H 100 F	B40	6WF	44	177.88	176.50	184	80	150	31.8	50	20
	45 H 100 F	B41	6WF	45	181.92	180.54	192	80	154	31.8	50	20
	48 H 100 F	B42	6WF	48	194.05	192.67	200	90	166	31.8	50	20
	60 H 100	-	6W	60	242.56	241.18	-	90	215	31.8	50	20
	72 H 100	-	6W	72	291.07	289.69	-	100	263	31.8	55	20

POULIES PRÉALÉSÉES

- H -

Pour courroie largeur 38,1 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	14 H 150 F	B14	6F	14	56.60	55.22	63	40	-	46	58	14
	15 H 150 F	B15	6F	15	60.64	59.26	66	45	-	46	58	14
	16 H 150 F	B16	6F	16	64.68	63.30	71	45	-	46	58	14
	17 H 150 F	B17	6F	17	68.73	67.35	75	45	-	46	58	14
	18 H 150 F	B18	6F	18	72.77	71.39	79	55	-	46	58	14
	19 H 150 F	B19	6F	19	76.81	75.43	83	60	-	46	58	14
	20 H 150 F	B20	6F	20	80.85	79.47	87	62	-	46	58	14
	21 H 150 F	B21	6F	21	84.90	83.52	91	65	-	46	58	14
	22 H 150 F	B22	6F	22	88.94	87.56	93	68	-	46	58	14
	23 H 150 F	B23	6F	23	92.98	91.60	97	72	-	46	58	20/14
	24 H 150 F	B24	6F	24	97.02	95.64	103	72	-	46	58	20/14
	25 H 150 F	B25	6F	25	101.07	99.69	106	72	-	46	58	20/15
	26 H 150 F	B26	6F	26	105.11	103.73	111	80	-	46	58	20/15
	27 H 150 F	B27	6F	27	109.15	107.77	115	80	-	46	58	20/15
	28 H 150 F	B28	6F	28	113.19	111.81	119	80	-	46	58	20/15
	29 H 150 F	B29	6F	29	117.24	115.86	123	80	-	46	58	20/15
	30 H 150 F	B30	6F	30	121.28	119.90	127	80	-	46	58	20/15
Fonte ou Acier	32 H 150 F	B32	6F	32	129.36	127.98	135	80	-	46	58	20
	34 H 150 F	B33/34	6F	34	137.45	136.07	142	80	-	46	58	20
	35 H 150 F	B35	6F	35	141.49	140.11	148	80	-	46	58	20
Fonte	36 H 150 F	B36	6F/6WF	36	145.54	144.16	152	80	118	46	58	20
	38 H 150 F	B37	6F/6WF	38	153.62	152.24	158	80	126	46	58	20
	40 H 150 F	B38	6F/6WF	40	161.71	160.33	168	80	134	46	58	20
	44 H 150 F	B40	6WF	44	177.88	176.50	184	80	150	46	58	20
	45 H 150 F	B41	6WF	45	181.92	180.54	192	80	154	46	58	20
	48 H 150 F	B42	6WF	48	194.05	192.67	200	90	166	46	65	20
	60 H 150	-	6W	60	242.56	241.18	-	90	215	46	65	20
	72 H 150	-	6W	72	291.07	289.69	-	100	263	46	65	20

Pour courroie largeur 50,8 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	14 H 200 F	B14	6F	14	56.60	55.22	63	40	-	58.7	70	20/15
	15 H 200 F	B15	6F	15	60.64	59.26	66	45	-	58.7	70	20/15
	16 H 200 F	B16	6F	16	64.68	63.30	71	45	-	58.7	70	20/15
	17 H 200 F	B17	6F	17	68.73	67.35	75	45	-	58.7	70	20/15
	18 H 200 F	B18	6F	18	72.77	71.39	79	55	-	58.7	70	20/15
	19 H 200 F	B19	6F	19	76.81	75.43	83	60	-	58.7	70	20/15
	20 H 200 F	B20	6F	20	80.85	79.47	87	62	-	58.7	70	20/15
	21 H 200 F	B21	6F	21	84.90	83.52	91	65	-	58.7	70	20/15
	22 H 200 F	B22	6F	22	88.94	87.56	93	68	-	58.7	70	20/15
	23 H 200 F	B23	6F	23	92.98	91.60	97	72	-	58.7	70	20/15
	24 H 200 F	B24	6F	24	97.02	95.64	103	72	-	58.7	70	20/15
	25 H 200 F	B25	6F	25	101.07	99.69	106	72	-	58.7	70	20/15
	26 H 200 F	B26	6F	26	105.11	103.73	111	80	-	58.7	70	20/15
	27 H 200 F	B27	6F	27	109.15	107.77	115	80	-	58.7	70	20/15
	28 H 200 F	B28	6F	28	113.19	111.81	119	80	-	58.7	70	20/15
	29 H 200 F	B29	6F	29	117.24	115.86	123	80	-	58.7	70	20/15
	30 H 200 F	B30	6F	30	121.28	119.90	127	80	-	58.7	70	20/15
Fonte ou Acier	32 H 200 F	B32	6F	32	129.36	127.98	135	80	-	58.7	10	20
	34 H 200 F	B33/34	6F	34	137.45	136.07	142	80	-	58.7	70	20
	35 H 200 F	B35	6F	35	141.49	140.11	148	80	-	58.7	70	20
Fonte	36 H 200 F	B36	6F/6WF	36	145.54	144.16	152	80	118	58.7	70	20
	38 H 200 F	B37	6F/6WF	38	153.62	152.24	158	80	126	58.7	70	20
	40 H 200 F	B38	6F/6WF	40	161.71	160.33	168	80	134	58.7	70	20
	44 H 200 F	B40	6WF	44	177.88	176.50	184	80	150	58.7	70	20
	45 H 200 F	B41	6WF	45	181.92	180.54	192	80	154	58.7	70	20
	48 H 200 F	B42	6WF	48	194.05	192.67	200	90	166	58.7	75	20
	60 H 200	-	6W	60	242.56	241.18	-	90	215	58.7	75	20
	72 H 200	-	6W	72	291.07	289.69	-	100	263	58.7	75	20

POULIES PRÉALÉSÉES

- H -

Pour courroie largeur 76,2 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Acier	14 H 300 F	B14	6F	14	56.60	55.22	63	40	-	85.7	100	-
	15 H 300 F	B15	6F	15	60.64	59.26	66	45	-	85.7	100	-
	16 H 300 F	B16	6F	16	64.68	63.30	71	45	-	85.7	100	-
	17 H 300 F	B17	6F	17	68.73	67.35	75	45	-	85.7	100	-
	18 H 300 F	B18	6F	18	72.77	71.39	79	55	-	85.7	100	-
	19 H 300 F	B19	6F	19	76.81	75.43	83	60	-	85.7	100	-
	20 H 300 F	B20	6F	20	80.85	79.47	87	62	-	85.7	100	-
	21 H 300 F	B21	6F	21	84.90	83.52	91	65	-	85.7	100	-
	22 H 300 F	B22	6F	22	88.94	87.56	93	68	-	85.7	100	-
	23 H 300 F	B23	6F	23	92.98	91.60	97	72	-	85.7	100	-
	24 H 300 F	B24	6F	24	97.02	95.64	103	72	-	85.7	100	-
	25 H 300 F	B25	6F	25	101.07	99.69	106	72	-	85.7	100	-
	26 H 300 F	B26	6F	26	105.11	103.73	111	80	-	85.7	100	-
	27 H 300 F	B27	6F	27	109.15	107.77	115	80	-	85.7	100	-
	28 H 300 F	B28	6F	28	113.19	111.81	119	80	-	85.7	100	-
	29 H 300 F	B29	6F	29	117.24	115.86	123	80	-	85.7	100	-
	30 H 300 F	B30	6F	30	121.28	119.90	127	80	-	85.7	100	-
	32 H 300 F	B32	6F	32	129.36	127.98	135	80	-	85.7	100	-
	34 H 300 F	B33/34	6F	34	137.45	136.07	142	80	-	85.7	100	-
	35 H 300 F	B35	6F	35	141.49	140.11	148	80	-	85.7	100	-
Fonte ou Acier	36 H 300 F	B36	6F/6WF	36	145.54	144.16	152	80	118	85.7	100	-/20
	38 H 300 F	B37	6F/6WF	38	153.62	152.24	158	80	126	85.7	100	-/20
	40 H 300 F	B38	6F/6WF	40	161.71	160.33	168	80	134	85.7	100	-/20
Fonte	44 H 300 F	B40	6WF	44	177.88	176.50	184	80	150	85.7	100	-/24
	45 H 300 F	B41	6WF	45	181.92	180.54	192	80	154	85.7	100	-/24
	48 H 300 F	B42	6WF	48	194.05	192.67	200	90	166	85.7	100	-/24
	60 H 300	-	6W	60	242.56	241.18	-	90	215	85.7	100	-/24
	72 H 300	-	6W	72	291.07	289.69	-	100	263	85.7	100	-/24

