

POULIES PRÉALÉSÉES

- XH -

Pour courroie largeur 50,8 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Fonte ou Acier	18 XH 200 F	B43	6F	18	127.34	124.55	138	100	-	63.2	80	24
	19 XH 200 F	B44	6F	19	134.42	131.63	145	100	-	63.2	80	24
	20 XH 200 F	B45	6F	20	141.49	138.70	154	100	-	63.2	80	24
	21 XH 200 F	B46	6F	21	148.57	145.78	160	110	-	63.2	80	24
	22 XH 200 F	B47	6F	22	155.64	152.85	168	110	-	63.2	80	24
	24 XH 200 F	B49	6F	24	169.79	167.00	183	120	-	63.2	80	24
	25 XH 200 F	B50	6F	25	176.87	174.08	188	120	-	63.2	80	24
	26 XH 200 F	B51/53	6F	26	183.94	181.15	198	120	-	63.2	80	24
	28 XH 200 F	B55	6F	28	198.09	195.30	211	150	-	63.2	80	24
	30 XH 200 F	B57	6F	30	212.24	209.45	225	150	-	63.2	80	24
Fonte	32 XH 200 F	B59/60	6F	32	226.39	223.60	240	150	-	63.2	80	24
	40 XH 200 F	B64	6WF	40	282.99	280.20	296	150	241	63.2	100	28
	48 XH 200	-	6W	48	339.58	336.79	-	150	297	65.1	100	28
	60 XH 200	-	6A	60	424.48	421.69	-	150	382	65.1	100	28

Pour courroie largeur 76,2 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Fonte ou Acier	18 XH 300 F	B43	6F	18	127.34	124.55	138	100	-	90.4	110	28
	19 XH 300 F	B44	6F	19	134.42	131.63	145	100	-	90.4	110	28
	20 XH 300 F	B45	6F	20	141.49	138.70	154	100	-	90.4	110	28
	21 XH 300 F	B46	6F	21	148.57	145.78	160	110	-	90.4	110	28
	22 XH 300 F	B47	6F	22	155.64	152.85	168	110	-	90.4	110	28
	24 XH 300 F	B49	6F	24	169.79	167.00	183	120	-	90.4	110	28
	25 XH 300 F	B50	6F	25	176.87	174.08	188	120	-	90.4	110	28
	26 XH 300 F	B51/53	6F	26	183.94	181.15	198	120	-	90.4	110	28
	28 XH 300 F	B55	6F	28	198.09	195.30	211	150	-	90.4	110	28
	30 XH 300 F	B57	6F	30	212.24	209.45	225	150	-	90.4	110	28
	32 XH 300 F	B59/60	6F	32	226.39	223.60	240	150	-	90.4	110	28
Fonte	40 XH 300 F	B64	6WF	40	282.99	280.20	296	150	241	90.4	120	32
	48 XH 300	-	6W	48	339.58	336.79	-	150	297	92.1	120	32
	60 XH 300	-	6A	60	424.48	421.69	-	150	382	92.1	120	32

POULIES PRÉALÉSÉES

- XH -

Pour courroie largeur 101,6 mm												
	Code	Flasques	Type	Dents	Dp	De	Df	Dm	Di	F	L	d
Fonte ou Acier	18 XH 400 F	B43	6F	18	127.34	124.55	138	100	-	117.3	132	32
	19 XH 400 F	B44	6F	19	134.42	131.63	145	100	-	117.3	132	32
	20 XH 400 F	B45	6F	20	141.49	138.70	154	100	-	117.3	132	32
	21 XH 400 F	B46	6F	21	148.57	145.78	160	110	-	117.3	132	32
	22 XH 400 F	B47	6F	22	155.64	152.85	168	110	-	117.3	132	32
	24 XH 400 F	B49	6F	24	169.79	167.00	183	120	-	117.3	132	32
	25 XH 400 F	B50	6F	25	176.87	174.08	188	120	-	117.3	132	32
	26 XH 400 F	B51/53	6F	26	183.94	181.15	198	120	-	117.3	132	32
	28 XH 400 F	B55	6F	28	198.09	195.30	211	150	-	117.3	132	32
	30 XH 400 F	B57	6F	30	212.24	209.45	225	150	-	117.3	132	32
	32 XH 400 F	B59/60	6F	32	226.39	223.60	240	150	-	117.3	132	32
Fonte	40 XH 400 F	B64	6WF	40	282.99	280.20	296	150	241	117.3	132	32
	48 XH 400	-	6W	48	339.58	336.79	-	150	297	119.1	132	32
	60 XH 400	-	6A	60	424.48	421.69	-	150	382	119.1	132	32

